

(12) United States Patent

Akasaka et al.

(10) Patent No.:

US 6,654,162 B2

(45) Date of Patent:

Nov. 25, 2003

(54) RAMAN AMPLIFIER, OPTICAL REPEATER, AND RAMAN AMPLIFICATION METHOD

Inventors: Youichi Akasaka, Chiyoda-ku (JP);

Yoshihiro Emori, Chivoda-ku (JP);

Shu Namiki, Chiyoda-ku (JP)

Assignce: The Furukawa Electric Co., Ltd.,

Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

Appl. No.: 09/886,212 (21)

(22)Filed: Jun. 22, 2001

Prior Publication Data (65)

US 2001/0046083 A1 Nov. 29, 2001

Related U.S. Application Data

Continuation of application No. 09/527,748, filed on Mar. 17, 2000, now Pat. No. 6,292,288, which is a continuation-in-part of application No. PCT/JP99/03944, filed on Jul. 23, 1999.

Foreign Application Priority Data (30)

Jul.	23, 1998	(JP)	
Jul.	27, 1998	(JP)	
Fcb.	12, 1999	(JP)	
Feb.	12, 1999	(JP)	11-034833
Jan.	14, 2000	(JP)	
(51)	Int. Cl.		H01S 3/30 ; G02B 6/28;
			H011 14/02

U.S. Cl. 359/334; 359/341.31; 372/3;

372/6 Field of Search 359/334, 337.1,

359/341.31, 341.32; 372/3, 6, 70

(56)References Cited

U.S. PATENT DOCUMENTS

4,616,898 A 10/1986 Hicks, Jr.

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

EP	0 615 356 A1 *	9/1994	359/156
JP	02-012986	1/1990	
JP	10-73852	3/1998	
wo	WO 98/42088	9/1998	
wo	98/42088	9/1998	

OTHER PUBLICATIONS

Nimicki et al, I.E.E.E. Journ. of Selected Topics In Quantum Electronics, vol. 7, #1, pp. 3-16, 1/01.*

(List continued on next page.)

Primary Examiner-Nelson Moskowitz (74) Attorney, Agent, or Firm-Oblon, Spivak, McClelland, Maier & Neustadt, P.C.

ABSTRACT

A Raman amplifier according to the present invention comprises a plurality of pumping means using semiconductor lasers of Fabry-Perot, DFB, or DBR type or MOPAs, and pumping lights outputted from the pumping means have different central wavelengths, and interval between the adjacent central wavelength is greater than 6 nm and smaller than 35 nm. An optical repeater according to the present invention comprises the above-mentioned Raman amplifier and adapted to compensate loss in an optical fiber transmission line by the Raman amplifier. In a Raman amplification method according to the present invention, the shorter the central wavelength of the pumping light the higher light power of said pumping light. In the Raman amplifier accord ing to the present invention, when a certain pumping wavelength is defined as a first channel, and second to n-th channels are defined to be arranged with an interval of about 1 THz toward a longer wavelength side, the pumping lights having wavelengths corresponding to the first to n-th channels are multiplexed, and an pumping light having a wavelength spaced apart from the n-th channel by 2 THz or more toward the longer wavelength side is combined with the multiplexed light, thereby forming the pumping light source. The pumping lights having wavelengths corresponding to the channels other than (n-1)-th and (n-2)-th channels may be multiplexed, thereby forming the pumping light source. The pumping lights having wavelengths corresponding to the channels other than (n-2)-th and (n-3)-th channels may be multiplexed, thereby forming the pumping light source.

122 Claims, 66 Drawing Sheets

